PRODUCT INFORMATION



Benchmark™

Foam Marking Agent

GENERAL INFORMATION

Benchmark foam marking agent is specially formulated to deliver long lasting foam in a range of weather and field conditions.

Benchmark is a highly concentrated formula, that when used as directed, will produce a thick, white, highly visible foam. This foam can be used with any foam marker equipment for fertilizer and pesticide applications, seed planting and general field cultivation.

Benchmark is formulated to handle extreme hard water and high temperature conditions.

USE RATES

Standard Use rate: Add 1 gallon of Benchmark for every 160 gallons of water; or 1/2 pint (8 fluid ounces) in every 10 gallons of water.

Adverse Conditions (such as hard water or high temperature):
Add 2 fluid ounces of Benchmark for every 1 gallon of solution reservoir capacity. Benchmark performs well in hard water up to 1,500 ppm.

Near Freezing Temperatures: Add 2 to 3 fluid ounces of methanol per gallon of Benchmark for immediate use. Benchmark mixes well in cold water.

Color additives: If foam colorant additive is being used, add 2 fluid ounces of Benchmark for every 1 gallon of solution reservoir capacity.

TECHNICAL INFORMATION

Net Weight: 98.67 lbs/gal Specific Gravity: 1.02-1.04 Flashpoint: >176°F SFCC pH: 7-9 (aqueous solution)

Color & Appearance: Clear Liquid

Odor: Sweet

Storage Temperature - Minimum: 32°F - DO NOT FREEZE!

Storage Temperature - Maximum: 120°F

DOT/IMDG Transporation (applies to containers greater than 119 gallons only): NA1993, Combustible Liquid, N.O.S. (ethylene

glycol monobutyl ether), 3, PG III

Marine Pollutant: No Registered With CDPR: N/A Registered With WSDA: N/A

PRINCIPAL FUNCTIONING AGENTS

Proprietary blend of active foam agents...100.00%



PACKAGING

4 x 1 gallon jugs 36 cases per pallet Item#: BMK01

30 gallon drum 5 drums per pallet Item#: BMK30

55 gallon drum 4 drums per pallet Item#: BMK55

