



Anti-Foam™

Antifoaming and Defoaming Agent

GENERAL INFORMATION

Anti-Foam is a fast, effective defoamer for use in suppressing foam. Controlling foam reduces filling time and lessens overflow waste. Anti-Foam improves spray performance. The combination of effective ingredients allows for very fast knockdown of troublesome foam if it should occur in the spray tank.

USE RATES

Read label before use. Anti-Foam should be added to the spray mixture before the pesticide or any additional surfactant is added. Agitation is recommended to aid in dispersion of the various components.

General Use Rate: Add 1 to 2 fluid ounces of Anti-Foam per 100 gallons of spray mixture.

For Recirculating Sprayers: Add 4 fluid ounces per 100 gallons of spray mixture.

If Foam Has Already Occurred: Add 6 fluid ounces per 100 gallons of spray mixture.

TECHNICAL INFORMATION

Net Weight: 8.50 lbs/gal

Specific Gravity: 0.98-1.02

Flashpoint: >212°F

pH: 3.5-4.5

Solubility in Water at 20°C: Soluble

Color & Appearance: Milky Off-White Emulsion

Odor: Bland

Storage Temperature - Minimum: 40°F

Storage Temperature - Maximum: 110°F

DOT Information: Not regulated

Registered With CDPR: Yes

Registered With WSDA: Yes

PRINCIPAL FUNCTIONING AGENTS

Polydimethylsiloxane,
silicon dioxide...10.0%



PACKAGING

12 x 1 quart bottles
10 cases per pallet
Item#: AF1Q

FeXapan™

Approved for use with FeXapan.
FeXapan is a trademark of Dupont.



Approved for use with Enlist Duo.
Enlist Duo is a trademark of DOW Chemical Co.



KALO

Anti-Foam is a trademark of KALO, Inc.
KALO, Inc., 13200 Metcalf Ave, Suite 250, Overland Park, KS 66213 • www.kalo.com
Important: This information is not a substitute for the label. Always read and follow label instructions.

Document Date: 05.04.17

© 2017 KALO, Inc.