Water-Rite_{IM}

Water-Rite_™

Nonionic Surfactant

Directions For Use

For Soil Moisture Management

Irrigation Systems: Use Water-Rite at 1 to 6 quarts per acre through any type of irrigation system. First application should coincide with first irrigation cycle. A follow-up application of 1 to 6 pints per acre is recommended two weeks after initial application. Continue with 1 to 6 pints per acre every 4 to 6 weeks. Always use back-flow prevention valve (check-valve) when injecting into irrigation systems.

Drip or Micro-Sprinkler Systems: Apply 1 to 6 quarts of Water-Rite per acre. Apply to coincide with first irrigation cycle. Two weeks after initial application, follow up with a second application of 1 to 6 pints per acre then follow with 1 to 6 pints per acre every 4 to 6 weeks. The final application of the season should be scheduled with the last full irrigation cycle.

IMPORTANT: Additional Operating Instructions for Chemigation. Review your state and local regulatory requirements before applying any adjuvant of agricultural chemical through an irrigation system. Refer to the SUPPLEMENTAL LABELING FOR CHEMIGATION APPLICATIONS below for additional use requirements and restrictions.

SUPPLEMENTAL LABELING FOR CHEMIGATION APPLICATIONS

General Directions For Chemigation

- Calibrate the irrigation and injection system before applying Water-Rite. Calibrate the
 injection pump with the irrigation system fully charged at the desired operating pressure.
 If you have questions about calibration, you should contact state extension specialists,
 equipment manufacturers, or other experts.
- A person knowledgeable of the chemigation system and responsible for its operation, or under the supervision of the responsible person, shall start up, operate, or shut down the system and make necessary adjustments should the need arise.
- Check the irrigation system to insure uniform application of water. The chemigation system, which is inclusive of the irrigation equipment and chemigation apparatus, must be properly maintained.
- Do not apply when system connections or fittings leak or when emitters or sprinkler heads are not properly functioning.
- The injection unit and supply tank should be equipped with an in-line strainer with a 100-mesh or larger screen positioned between the supply tank and the injection pump. Dispose of any residue in accordance with Federal or State laws.
- The irrigation system must contain a functional check valve, vacuum relief valve, inspection port, and low-pressure drain that are appropriately sized and located on the irrigation mainline to prevent water source contamination from back-flow. The adjuvant (pesticide) injection line must contain a functional, automatic, quick-closing check valve to prevent the flow of fluid back toward the injection pump. The adjuvant (pesticide) injection line must also contain a functional, normally closed solenoid-operated valve located on the intake side of the injection pump and connected to the system interlock to prevent fluid from being withdrawn from the supply tank when the irrigation system is either automatically or manually shutdown. The system must contain functional interlocking controls to automatically shut off the adjuvant (pesticide) injection pump when the water pump motor stops. The irrigation mainline or water pump must include a functional pressure switch that will stop the water pump motor when the water pressure decreases to the point where pesticide distribution is adversely affected. Systems must use a metering pump, such as a positive displacement injection pump (e.g., diaphragm or piston pump), effectively designed and constructed of materials that are compatible with pesticides and capable of being fitted with a system interlock.
- Add specified amount of Water-Rite to the water in the supply tank. Application should be in sufficient water and of sufficient duration to apply the recommended rate evenly.
- Start the water pump and irrigation system, allowing the desired pressure to be achieved throughout the irrigation system before starting the injection process.
- · Apply continuously for the duration of the application period.

- Do not allow irrigation water to collect or run-off during chemigation and pose a hazard to workers, bystanders, livestock, wells, or adjoining crops.
- Once the application is completed, thoroughly flush the entire irrigation and injection system with untreated water before turning off the irrigation system. To ensure the lines are flushed and free of this product, a dye indicator may be injected into the lines to mark the end of the application period.
- Wear required Personal Protective Equipment when making adjustments or repairs on the chemigation system when Water-Rite is in the irrigation water or residue may be present.
- Do not apply when wind-speed favors drift beyond the area intended for treatment. Do
 not apply when wind speed favors drift, when system connection or fittings leak, when
 sprinkler heads or emitters do not provide uniform distribution or when lines containing
 the product must be dismantled and drained.

Using Water From Public Water Systems

Public water system means a system for the provision to the public of piped water for human consumption if such system has at least 15 service connections or regularly serves an average of at least 25 individuals daily at least 60 days out of the year. Chemigation systems connected to public water systems must contain a functional, reduced-pressure zone (RPZ), back-flow preventer or the functional equivalent in the water supply line upstream from the point of adjuvant (pesticide) introduction. As an option to the RPZ, the water from the public water system should be discharged into a reservoir tank prior to adjuvant (pesticide) introduction. There shall be a complete physical break (air gap) between the flow outlet end of the fill pipe and the top or overflow rim of the reservoir tank of at least twice the inside diameter of the fill pipe.

• Do not connect an irrigation system (including greenhouse systems) used for adjuvant (pesticide) application to a public water system unless the label-prescribed safety devices for public water supplies are in place.

Additional Operating Instructions for Chemigation

- Any alternatives to the above required safety devices must conform to the "List of EPAapproved Alternative Devices."
- Refer to the American Society of Agricultural Engineer's Engineering Practice 409.1 for more information about back-flow safety devices.

California State Reg. No. 45989-50029-AA Washington State Reg. No. 45989-11001



Water-Rite is a trademark of KALO, Inc.

CONDITIONS OF SALE, LIMITED WARRANTY, AND LIMITATIONS OF LIABILITY AND REMEDIES
Read the Conditions of Sale — Warranty and Limitations of Liability and Remedies before using this product. If
the terms are not acceptable, return the product, unopened, and the full purchase price will be refunded. The
directions of this label are believed to be reliable and should be followed carefully. Insufficient control of pests
and/or injury to crop to which the product is applied may result from the occurrence of extraordinary or unusual
weather conditions or the failure to follow the label directions or good application practices, all of which are
beyond the control of KALO, Inc., the manufacturer or seller. In addition, failure to follow label directions may
cause injury to crops, animals, workers or the environment. The Company warrants that this product conforms
to the chemical description on the label and is reasonably fit for the purpose referred to in the directions for
use subject to the factors noted above which are beyond the control of the Company. The Company makes
no other warranties or representations of any kind express or implied concerning the product, including no
implied warranty of merchantability or fitness for any particular purpose, and no such warranty shall be implied
by law. The exclusive remedy against the Company for any cause of action relating to the handling or use of
this product shall be limited to, at KALO, Inc.'s election, one of the following:

- 1. Refund of the purchase price paid by buyer or user for product purchased
- 2. Replacement of the product used.

To the extent allowed by law, the Company shall not be liable and any and all claims against the Company are waived for special, indirect, incidental, or consequential damages or expense of any nature, including, but no limited to, loss of profits or income. The Company, the manufacturer and seller offer this product and the buyer and user accept it, subject to the foregoing conditions of sale and limitation of warranty, liability and remedies.



KALO, Inc.

13200 Metcalf Ave., Suite 250, Overland Park, KS 66213 800-255-5196 • www.kalo.com

Scan QR Code to open KALO's Labels & SDS page on www.kalo.com